

## Solenoid operated poppet valve stainless

### Flange construction

- ◆ 2/2- or 3/2-way
- ◆ normally open and normally closed
- ◆  $Q_{max} = 40 \text{ l/min}$
- ◆  $p_{max} = 350 \text{ bar}$

### DESCRIPTION

Direct operated 2/2- and 3/2-way poppet valve in flange construction. By means of the pressure tight switching solenoid, the poppet valve spool is opened or closed acting against the spring. Due to the poppet spool construction with pressure compensation on both sides, the flow through the valve is possible in both directions. The metallically sealing seat closes the valve virtually leak free. The pressure tight encapsulated Ex-protection solenoid coil prevents an explosion on the inside penetrating to the outside as well as an ignitable surface temperature.

### CERTIFICATES

	Surface	Mining	Standard -25 °C to...	Z604 -40 °C to...
ATEX / UKEX	x	x	x	x
IECEX	x	x	x	x
CCC	x	x	x	x
EAC	x	x	x	x
Australia	x	x	x	x
MA		x	x	
USA / Canada	x		x	x
PESO	x		x	x

The certificates can be found on [www.wandfluh.com](http://www.wandfluh.com)

### NG6

#### ISO 4401-03

Ex db IIC T6, T4 Gb (Zone 1)

Ex tb III C T80 °C, T130 °C Db (Zone 21)

Ex db I Mb


⊕ II 2 G Ex db IIC T6, T4

⊕ II 2 D Ex tb III C T80 °C, T130 °C

⊕ I M2 Ex db I Mb

Class I, Division 1, Group A, B, C, D T4

Class II & III, Division I, Group E, F, G T4



### APPLICATION

These valves are suitable for applications in explosion-hazard areas, open cast and also in mines. The stainless execution is especially suitable for the use in wet and salty environment. Poppet valves are used where tight closing functions of the valve are essential like leakage-free load holding, clamping or gripping.

### ACTUATION

Actuation	Switching solenoid, wet pin push type, pressure tight
Execution	MKY45 / 18x60 (data sheet 1.1-183)
Connection	Cable gland for cable Ø 6,5...14 mm

**Attention!** The UC execution is always supplied without cable gland




### STANDARDS


Explosion protection	Directive 2014 / 34 / EU (ATEX)
Flameproof enclosure	EN / IEC / UL 60079-1, 31
Cable entry	EN 60079-0, 1, 7, 15, 31
Mounting interface	ISO 4401-03
Protection class	EN 60 529
Contamination efficiency	ISO 4406

### SYMBOL


A.22060b




A.22061a



A.32060b



A.32061a



**TYPE CODE**

International standard interface ISO		A Exd <input type="checkbox"/> 2 06 <input type="checkbox"/> - <input type="checkbox"/> / <input type="checkbox"/> / <input type="checkbox"/> - <input type="checkbox"/> <input type="checkbox"/> # <input type="checkbox"/>	
Explosion-proof execution, Ex d			
2 way (connections)	<input type="checkbox"/>		
3 way (connections)	<input type="checkbox"/>		
2 switching positions			
Nominal size 6			
Normally closed	Solenoid on A-side	<input type="checkbox"/>	
Normally open	Solenoid on B-side	<input type="checkbox"/>	
Nominal voltage $U_N$	12 VDC	<input type="checkbox"/>	115 VAC
	24 VDC	<input type="checkbox"/>	230 VAC
Nominal power $P_N$	9 W	<input type="checkbox"/>	Ambient temperature up to: 40 °C or 90 °C
	15 W	<input type="checkbox"/>	70 °C
Certification	ATEX, UKEX, IECEX, EAC, CCC	<input type="checkbox"/>	USA / Canada
	Australia	<input type="checkbox"/>	India
	MA	<input type="checkbox"/>	
Sealing material / Temperature range	NBR	<input type="checkbox"/>	
	FKM (Viton)	<input type="checkbox"/>	
	NBR -40 °C	<input type="checkbox"/>	(only with 15 W)
Stainless	with K8 coil	<input type="checkbox"/>	
	with K9 coil	<input type="checkbox"/>	

Design index (subject to change)

1.11-3143S


**GENERAL SPECIFICATIONS**

Designation	2/2-, 3/2-way poppet valve
Construction	Direct operated
Mounting	Flange construction
Nominal size	NG6 according to ISO 4401-03
Actuation	Ex-protection switching solenoid
Ambient temperature	<b>Operation as T6</b> -25...+40 °C (L9) <b>Operation as T4</b> -25...+90 °C (L9) -25...+70 °C (L15) -40...+70 °C (L15)
Weight	3,3 kg
MTTFd	150 years


**HYDRAULIC SPECIFICATIONS**

Working pressure	$p_{max} = 350$ bar
Maximum volume flow	$Q_{max} = 40$ l/min, see characteristic
Volume flow direction	Any (see characteristic)
Leakage oil	Poppet type, max. 0,05 ml / min (approx. 1 drop / min) at 30 cSt
Fluid	Mineral oil, other fluid on request
Viscosity range	12 mm <sup>2</sup> /s...320 mm <sup>2</sup> /s
Temperature range fluid	<b>Operation as T6</b> NBR -25...+40 °C (L9) FKM -20...+40 °C (L9) <b>Operation as T4</b> NBR -25...+70 °C (L9 or L15) FKM -20...+70 °C (L9 or L15) NBR 872 -40...+70 °C (L15)
Contamination efficiency	Class 20 / 18 / 14
Filtration	Required filtration grade $\beta_{10} \dots \beta_{16} \geq 75$ , see data sheet 1.0-50


## PERFORMANCE SPECIFICATIONS


 Oil viscosity  $\nu = 30 \text{ mm}^2/\text{s}$ 


Type	Flow direction			
	P - A	A - T	A - P	T - A
AEXd22061a	1	-	6	-
AEXd22060b	1	-	3	-
AEXd32061a	1	2	5	1
AEXd32060b	1	4	7	1



Type	Flow direction			
	P - A	A - T	A - P	T - A
AEXd22061a	1	-	6	-
AEXd22060b	1	-	3	-
AEXd32061a	1	2	5	1
AEXd32060b	1	4	7	1



**Note!**  With the L15 execution for ambient temperatures up to 70 °C, the performance specifications have been evaluated with an ambient temperature of 50 °C

**Attention!**  Long periods of non-actuation can reduce the switching performance

### SURFACE TREATMENT

-The valve body, the cover and the socket head screws are made of stainless steel

-The slip-on coil and the armature tube are zinc nickel coated

#### Optionally K10:

-The coil is made of stainless steel

### VALVES INSTALLED

The central functioning element is the poppet valve cartridge NG6, data sheet 1.11-2030.

## ELECTRICAL SPECIFICATIONS

Protection class	IP65 / 66 / 67
Relative duty factor	100 % DF
Switching frequency	12'000 / h
Voltage tolerance	$\pm 10 \%$ with regard to nominal voltage
Standard nominal voltage	12 VDC, 24VDC, 115 VAC, 230 VAC AC = 50 to 60 Hz $\pm 2 \%$ , with built-in two-way rectifier
Standard nominal power	9 W, 15 W
Temperature class	Nominal power 9 W: T1...T6 Nominal power 15 W: T1...T4

**Note!**  Other electrical specifications see data sheet 1.1-183

### SEALING MATERIAL

NBR or FKM (Viton) as standard, choice in the type code



### MANUAL OVERRIDE

Screw plug (HB0), no actuation possible

Optionally: HB6, HN(K) or HG(K)

→ See data sheet 1.1-311


## DIMENSIONS



**Note!** The K9 coil (K10 valve) is 1 mm larger than the valve body. Usually, a distance plate is necessary.



## HYDRAULIC CONNECTION



Dimensions of the solenoid coil see data sheet 1.1-183 and 1.1-183S

## PARTS LIST

Position	Article	Description
10	263.6...	Solenoid coil MK.45 / 18 x 60
12	154.2201	Knurled nut Ex M18 x 1,5 x 30
17	160.2251	O-ring ID 25,07 x 2,62 (NBR)
18	160.2170	O-ring ID 17,17 x 1,78 (NBR)
40	058.4221	Cover 45 /45 x 17,5 K9
60	246.2516	Socket head screw M5 x 16 A4 DIN 912
70	160.2093	O-ring ID 9,25 x 1,78 (NBR) „-25 °C to...”
	160.7092	O-ring ID 9,25 x 1,78 (NBR) „-40 °C to...”
	160.6092	O-ring ID 9,25 x 1,78 (FKM)
110	111.1080	Cable gland M20 x 1,5

## INSTALLATION NOTES

Mounting type	Flange mounting 4 fixing holes for socket head screws M5 x 45
Mounting position	Any, preferably horizontal
Tightening torque	Fixing screws $M_D = 5,1 \text{ Nm}$ (screw quality A4) $M_D = 9 \text{ Nm}$ knurled nut

**Note!** The length of the fixing screw depends on the base material of the connection element.



**Attention!** For stack assembly please observe the remarks in the operating instructions



## COMMISSIONING

**Attention!** The solenoid coil must only be put into operation, if the requirements of the operating instructions supplied are observed to their full extent. In case of non-observance, no liability can be assumed.



## ACCESSORIES

Technical explanations	Data sheet 1.0-100
Filtration	Data sheet 1.0-50
Relative duty factor	Data sheet 1.1-430